

ANDUBLABES



CERAMIC TILE BLADE

 $\ensuremath{\mathsf{DESCRIPTION}}$: A range of continuous rim tile saw blades for angle grinders and fixed machines.

USE ME FOR: All types of ceramic and stone tiles. Can be used dry up to 125mm but water is recommended above this dimension.

10MM SEGMENT HEIGHT

CONTINUOUS RIM / STANDARD CORE

CAN BE USED DRY UP TO 125MM

SINTERED BOND / REDUCED CHIPPING

GREAT SPEED OF CUT & LIFE





MATERIAL TYPE

GLASS / REINFORCED PLASTIC POLYURETHANE

HARD DENS

MATERIA

	FIBREGLASS	
	MARBLE - DRY CUTTING	
ı	STEEL BARS, PIPE & SECTIONS	
	SG & GREY IRON	
	PORCELAIN & HARD TILES	
	CERAMIC TILES	
	INDIAN STONE	
	GRANITE	
	SLATE	
	CLASS A ENGINEERING BRICKS	
	CLAY PAVIORS / PIPES / TILES	
	FLINT AGGREGATE PRODUCT	
	CLASS B ENGINEERING BRICKS	
	HEAVILY REINFORCED CONCRETE	
	MEDIUM REINFORCED CONCRETE	
	LIGHTLY REINFORCED CONCRETE	
	CONCRETE	
	HARD YORK STONE	
	QUARTZITE	
	LONDON BRICK	
	HARD CONCRETE PRODUCTS	
	KERBS / LINTELS / BEAMS	
	CAST PIPES	
	BRICKS / CONCRETE FLAGS	
	HAND MADE BRICKS	
	FACING BRICKS	
	CONCRETE ROOF TILES	
Ī	SOFT CONCRETE PAVIORS	
	SAND BASED PAVIORS	
	GREEN CONCRETE	
,	CEMENT SCREED	
	LIGHTWEIGHT CONCRETE BLOCK	
	HOT ROLLED ASPHALT	
	ABRASIVE SAND / GRITSTONE	
E	ASPHALT OVER CONCRETE	
-	ACRIALT	 1

PORCELAIN & CERAMIC TILES	PLUS
DIMENSIONS	DPT
(4½") 115 X 1.6 X 22.2 mm	115DPT
(5") 125 X 1.6 X 22.2 mm	125DPT
(6") 150 X 1.6 X 25.4 mm	150DPT
(7") 180 X 1.6 X 25.4 mm	180DPT
(8") 200 X 1.6 X 25.4 mm	200DPT
(9") 230 X 1.8 X 25.4 mm	230DPT
(10") 250 X 1.8 X 25.4 mm	250DPT
(12") 300 X 2.4 X 25.4 mm	300DPT
(14") 350 X 3.4 X 25.4 mm	350DPT
(14) 555 X 5.4 X 25.4 IIIII	COCDI I



HIGHLY SUITED

ASPHALT ABRASIVE MORTAR

NOT SUITABLE SUITABLE WITH RESERVATIONS